



TECHNICAL REFERENCE SHEET

Biscuit & Rusk Packing Machine (AR-300)

Complete technical specifications and installation reference.

MACHINE DIAGRAM

Placeholder

SPECIFICATION	VALUE
Start / Stop	Soft start and soft stop
Size of Pack (L x W x H)	80-200 x 10-75 x 40-80 mm
Machine Dimensions (L x W x H)	3990 x 1650 x 1650 mm
Machine Weight	1,000 KG
Film Reel (Outer / Core Diameter)	300 / 70 mm
Conveyor Length	10 ft
Machine Capacity	Up to 80-100 packs / minute
Electric Motor	1 HP + 0.5 HP
Machine Load	10 Amp (2 kW)
Standard Equipment	Photo electric eye and inverter
Packing Material	Food grade packaging film
Voltage & Frequency	220 VAC, Single Phase, 50 Hz
Packing Weight	2 g - 500 g
Sealing Type	2 Side and centre sealing
Heater Size	4 in - 6 in
Usage / Application	Biscuits, rusk, crackers and dry bakery stacks

INSTALLATION REQUIREMENTS



Stable floor level and operator access around the machine.



Electrical connection according to voltage and load specification.



Clean production environment with suitable packaging film storage.



Trained operator for safe production and routine inspection.

OPERATING CONDITIONS



Machine speed depends on product size, film type and feeding stability.



Final configuration should be confirmed with product samples.



Preventive maintenance and spare parts support available.



CONTACT INFORMATION

AL RAHEEM ENGINEERING

Website arengineering.com

Email info@arengineering.com

Phone 0303-4142423

Address Iqbal Chowk, Ashayana Road, Bank Stop, Lahore, Pakistan