



TECHNICAL REFERENCE SHEET

Candy Packing Machine (AR-800)

Complete technical specifications and installation reference.

MACHINE DIAGRAM
Placeholder

SPECIFICATION	VALUE
Start / Stop	Soft start and soft stop
Size of Pack (L x W x H)	Dynamic according to candy and sachet format
Machine Dimensions (L x W x H)	Industrial high-speed candy packing line
Machine Weight	1,400 KG
Film Reel (Outer / Core Diameter)	300 / 70 mm
Conveyor Length	Configured according to product feeding
Machine Capacity	Up to 800 packs / minute
Electric Motor	2 HP + 0.5 HP
Machine Load	15 Amp (2.8 kW)
Standard Equipment	Photo electric eye and inverter
Packing Material	Food grade packaging film
Voltage & Frequency	440 VAC, 3 Phase, 50 Hz
Packing Weight	2 g - 200 g
Sealing Type	3 Side and centre sealing
Heater Size	Configured according to sealing width
Usage / Application	Candy, toffee, confectionery and small sachets



INSTALLATION REQUIREMENTS



Stable floor level and operator access around the machine.



Electrical connection according to voltage and load specification.



Clean production environment with suitable packaging film storage.



Trained operator for safe production and routine inspection.

OPERATING CONDITIONS



Machine speed depends on product size, film type and feeding stability.



Final configuration should be confirmed with product samples.



Preventive maintenance and spare parts support available.



CONTACT INFORMATION

AL RAHEEM ENGINEERING

Website arengineering.com

Email info@arengineering.com

Phone 0303-4142423

Address Iqbal Chowk, Ashayana Road, Bank Stop, Lahore, Pakistan